

# evo<sup>2</sup>

DIESEL



**Snow tank volume**  
4.1 m<sup>3</sup> / compacted 5.1 m<sup>3</sup>



**Water tank volume**  
1,450 l or 1,600 l or 2,200 l  
+ Snow tank-water tank connection  
2,800 l or 2,950 l



**Blade width**  
2,300 mm or 2,500 mm  
Blade change < 60 seconds



**Fields of operations**  
Pro / Heavy duty

## DIESEL



<b>Engine</b>	Hatz 4H50TICD, 4 cylinder 1,952 cm <sup>3</sup>
<b>Power</b>	55.4 kW / 74.3 HP - 2,800 rpm

## FACTS & FIGURES

<b>Torque</b>	240 Nm - 1,600 rpm
<b>Exhaust gas treatment</b>	DOC, DPF with EGR Emission Stage V / EPA Tier 4 final
<b>Unloaded weight</b>	3,750 kg (basic outfit)
<b>Water tank</b>	1,450 l optional 1,600 l or 2,200 l
<b>Snow tank</b>	4.1 m <sup>3</sup> - compacted 5.1 m <sup>3</sup>
<b>Transmission</b>	Continuously adjustable hydraulic all-wheel drive
<b>Fuel tank</b>	52 l
<b>Hydraulic oil tank</b>	65 l
<b>Speed</b>	0 - 16 km/h
<b>Tyres</b>	225 / 75 / R16 C 6 rows of spikes
<b>Wheel rims</b>	8" x 16"



## STANDARD EQUIPMENT

Cab with heated windshield in safety glass,  
windscreen wiper system and interior light

---

PLC control

---

7 inch colour display

---

USB port for installing updates and data exchange

---

Button for automatic mode: Operations start  
automatically in a predefined order

---

Spring-suspended and height-adjustable driver's  
seat (fabric)

---

Armrest with storage capacity

---

Power steering

---

Easily-accessible engine compartment (tiltable)  
with cab support

---

Hydraulic oil cooler

---

Water and fuel tank made of PE

---

Function for automatic water filling system with  
immobilizer (Acquastop valve as optional)

---

Coated snow tank

---

Snow bin & water tank connection (> 2,800 l)

---

Footbrake and parking brake

Hydraulically driven and swivelling side brush

---

Board guide pulley

---

Side mirror, rear

---

Front headlights, snow bin headlight, side headlight

---

Flashing warning light

---

Acoustic signal for reverse drive, snow bin cover  
operation, reverse of the screw conveyors and blade  
exchange

---

Proportional water metering

---

System for water dosing in curves

---

Planing system made of stainless steel

---

Constant grinding pressure planing system

---

Quick-Change-System for fast blade replacement  
(< 60 seconds)

---

2 blades in wooden transport box  
(super-light blade - 3.5 kg)

---

2 towels

---

Scope of delivery-set



**suva**  
CERTIFICATION

In compliance with Suva certification  
no. E 7139/2.e



**Snow tank volume**  
4.1 m<sup>3</sup> / compacted 5.1 m<sup>3</sup>



**Water tank volume**  
1,450 l or 1,600 l  
or 2,200 l



**Blade width**  
2.300 mm or 2,500 mm



**Fields of operations**  
Pro / Heavy duty



# evo<sup>2</sup>



WM evo<sup>2</sup>  
Max Aicher Arena



WM technics GmbH  
Breiener Straße 15  
I-39053 Blumau  
Tel. +39 0471 353 332  
info@wm-technics.com

[www.wm-technics.com](http://www.wm-technics.com)



Mobile / Event

Pro / Heavy duty



Compact



evo<sup>2</sup>